

MATERIAL SAFETY 3M  
 DATA SHEET 3M Center  
 St. Paul, Minnesota  
 55144-1000  
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.  
 All rights reserved. Copying and/or downloading of this  
 information for the purpose of properly utilizing 3M products  
 is allowed provided that:

- 1) the information is copied in full with no changes unless  
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise  
 distributed with the intention of earning a profit thereon.

DIVISION: ENGINEERED ADHESIVES

TRADE NAME:

3M(TM) Fastbond(TM) Contact Adhesive 30-NF Green

ID NUMBER/U.P.C.:

62-4276-5530-3	00-21200-21184-3	62-4276-5535-2	00-21200-85829-1
62-4276-5538-6	00-21200-31347-9	62-4276-6530-2	00-21200-21185-0
62-4276-6535-1	- - -	62-4276-7530-1	00-21200-21186-7
62-4276-7535-0	- - -	62-4276-8530-0	00-21200-21187-4
62-4276-8535-9	00-21200-21187-3	62-4276-9530-9	00-21200-21188-1
62-4276-9531-7	- - -	62-4276-9535-8	00-21200-21188-0
62-4276-9930-1	00-21200-85826-0	62-4276-9932-7	00-21200-31344-8
62-4276-9935-0	00-21200-85827-7		

ISSUED: November 28, 2001

SUPERSEDES: May 24, 2001

DOCUMENT: 10-2979-2

1. INGREDIENT	C.A.S. NO.	PERCENT
WATER.....	7732-18-5	40.0 - 50.0
POLYCHLOROPRENE.....	9010-98-4	30.0 - 40.0
GLYCEROL ESTER OF HYDROGENATED ROSIN....	65997-13-9	5 - 10.0
TERPENE PHENOLIC RESIN.....	68648-57-7	5 - 10.0
TOLUENE.....	108-88-3	< 3.0
METHYL ALCOHOL.....	67-56-1	< 2.5
ZINC OXIDE.....	1314-13-2	< 2

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24  
 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT.  
 The components of this product are in compliance with the chemical  
 notification requirements of TSCA.

This product contains the following toxic chemical or chemicals subject to  
 the reporting requirements of Section 313 of Title III of the Emergency  
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

TOLUENE  
 METHYL ALCOHOL  
 ZINC OXIDE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
2. PHYSICAL DATA  
-----

BOILING POINT:..... 147.00 F  
(methanol)  
VAPOR PRESSURE:..... N/A  
VAPOR DENSITY:..... 1.10 Air=1  
EVAPORATION RATE:..... > 1.00 Ether=1  
SOLUBILITY IN WATER:..... Good  
SPECIFIC GRAVITY:..... 1.100 Water=1  
PERCENT VOLATILE:..... 50.00 % by wt  
pH:..... ca. 10.00  
VISCOSITY:..... 200.0 - 600.0 centipoise  
MELTING POINT:..... N/D

APPEARANCE AND ODOR:  
liquid, green, slight odor of ammonia

-----  
3. FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT:..... None  
FLAMMABLE LIMITS - LEL:..... N/A  
FLAMMABLE LIMITS - UEL:..... N/A  
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:  
Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:  
Wear full protective clothing, including helmet, self-contained,  
positive pressure or pressure demand breathing apparatus, bunker coat  
and pants, bands around arms, waist and legs, face mask, and  
protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:  
Not applicable.

NFPA HAZARD CODES: HEALTH: 1 FIRE: 0 REACTIVITY: 0  
UNUSUAL REACTION HAZARD: none

-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:  
Not applicable.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
4. REACTIVITY DATA (continued)  
-----

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Hydrogen Chloride, Aldehydes,  
Ketones.

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding  
physical and health hazards, respiratory protection, ventilation, and  
personal protective equipment. Cover with absorbent material.  
Collect spilled material. Place in a U.S. DOT-approved container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility in the presence of  
a combustible material. Dispose of completely cured (or polymerized)  
material in a sanitary landfill.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 37 gms/liter Tested per EPA Method 24.  
VOC Less H2O & Exempt Solvents: 77 gms/liter Tested per EPA Method 24.  
Hazardous Air Pollutants: ca. 0.09 #/# solids calculated (4.6% by  
weight)..

Since regulations vary, consult applicable regulations or authorities  
before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S.  
EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: No

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate  
medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get  
medical attention.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
6. SUGGESTED FIRST AID (continued)  
-----

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:

Avoid eye contact with vapor, spray, or mist. Wear vented goggles. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: nitrile rubber, polyethylene/ethylene vinyl alcohol, polytetrafluoroethylene (Teflon), fluoroelastomer (Viton).

RECOMMENDED VENTILATION:

Use with functioning spray booth or local exhaust. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Keep container closed when not in use. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
-----	-----	-----	-----	-----	-----
WATER.....	NONE	NONE	NONE	NONE	
POLYCHLOROPRENE.....	NONE	NONE	NONE	NONE	
GLYCEROL ESTER OF HYDROGENATED ROSIN.....	NONE	NONE	NONE	NONE	
TERPENE PHENOLIC RESIN.....	NONE	NONE	NONE	NONE	
-----	-----	-----	-----	-----	-----

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
TOLUENE.....	50	PPM	TWA	ACGIH	Y
TOLUENE.....	100	PPM	TWA	OSHAV	
		OSHA VACATED PEL			
TOLUENE.....	150	PPM	STEL	OSHAV	
		OSHA VACATED PEL			
TOLUENE.....	200	PPM	TWA	OSHA	
TOLUENE.....	300	PPM	CEIL	OSHA	
TOLUENE.....	75	PPM	STEL	CMRG	Y
METHYL ALCOHOL.....	200	PPM	TWA	ACGIH	Y
METHYL ALCOHOL.....	250	PPM	STEL	ACGIH	Y
METHYL ALCOHOL.....	200	PPM	TWA	OSHA	Y
METHYL ALCOHOL.....	250	PPM	STEL	OSHA	Y
ZINC OXIDE.....	10	MG/M3	TWA	ACGIH	
		AS DUST			
ZINC OXIDE.....	10	MG/M3	TWA	OSHAV	
		AS DUST			
		OSHA VACATED PEL			
ZINC OXIDE.....	5	MG/M3	TWA	ACGIH	
		as fume			
ZINC OXIDE.....	10	MG/M3	STEL	ACGIH	
		as fume			
ZINC OXIDE.....	5	MG/M3	TWA	OSHA	
		as fume			
ZINC OXIDE.....	10	MG/M3	STEL	OSHAV	
		as fume			
		OSHA VACATED PEL			
ZINC OXIDE.....	15	MG/M3	TWA	OSHA	
		AS TOTAL DUST			
ZINC OXIDE.....	5	MG/M3	TWA	OSHA	
		RESPIRABLE			

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL. Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- NONE: None Established

-----  
 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
8. HEALTH HAZARD DATA  
-----

EYE CONTACT:

Mild Eye Irritation: signs/symptoms can include redness, swelling, pain, and tearing.

SKIN CONTACT:

Contact with the skin during product use is not expected to result in significant irritation.

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

INHALATION:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Ingestion may cause:

Blindness.

REPRODUCTIVE/DEVELOPMENTAL TOXINS:

WARNING: Contains a chemical which can cause birth defects. (108-88-3)

-----  
SECTION CHANGE DATES  
-----

PRECAUTIONARY INFO. SECTION CHANGED SINCE May 24, 2001          ISSUE

-----  
Abbreviations: N/D - Not Determined    N/A - Not Applicable    CA - Approximately  
-----

-----

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.