



**Pawling Corporation**  
32 Nelson Hill Road  
PO Box 200  
Wassaic, NY 12592  
*sales@pawling.com*

Tel. 800-431-3456  
Fax 800-377-4403  
Tel. 845-373-9300  
Fax 845-373-7827

**ARCHITECTURAL PRODUCTS DIVISION**

Wall Protection Systems  
Entrance Mats And Gratings  
Athletic Flooring Systems  
Industrial Impact Protection Systems  
Parking And Traffic Safety Products

## **MR Credit 4.1/4.2 Recycled Content, CGT-7 Corner Guard**

The CGT-7 flush mounted corner guard consists an extruded aluminum retainer and an extruded thermoplastic snap-on cover. The cover is designed to work in conjunction with the retainer such that the assembly will absorb significant impact without damage to the materials or surrounding construction.

The recycled content of this product is given as a percentage calculated by comparing the weight of the product to the weight of the recycled materials it contains. The net weight of the corner guard assembly is 1.28 pounds per linear foot. This value represents the sum of the weights of retainer and cover extrusions combined and is subject to variation resulting from standard manufacturing tolerances.

The recycled content of this corner guard is contained solely in the retainer as follows:

Post Consumer Scrap:	10%
Post Industrial Scrap:	60%
Primary Aluminum:	30%

In accordance with guidelines set forth in USGBC – LEED V2.2, the recycled content of the retainer is:

$$\text{Post-Consumer} + 1/2 * \text{Pre-Consumer} = 10\% + 1/2 * 60\% = 40\%$$

Applying this percentage to the weight of the retainer, the recycled content of the corner guard assembly is 28% of the product by weight  $((40\% * .88) / 1.28 = 28\%)$ . This value may be applied to the project cost of this product and added to similar values for the total project in order to determine LEED credit applicability for MR Credits 4.1 and 4.2.