



# Millwork® Wall Finishing System

Wallbase, Chair Rail, Corner Guard, and Quarter Round & Shoe Moulding

# Product Specification

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Millwork Wall Finishing System profiles replicate the look of finely milled wood.

### 1.2. Manufacturer:

Tarkett North America      Phone (800) 899-8916  
 30000 Aurora Rd.  
 Solon, Ohio 44139  
 Web: [www.tarkett.com](http://www.tarkett.com)  
 E-mail: [info@tarkett.com](mailto:info@tarkett.com)

### 1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Millwork Resilient Wall Base is manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861 Standard Specification for Resilient Wall Base, Type TP, and Group 1.

### 1.3.2. Physical Characteristics (Millwork Wallbase):

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
<b>Ambassador</b> (MW-XX-K)	3/8" x 4" x 8' (9.52mm x 10.16cm x 2.44m)	6	48 (14.6m)	34.8 (15.8 kg)
<b>Attaché</b> (MW-XX-E)	1/4" x 6" x 8' (6.35mm x 15.24cm x 2.44m)	8	64 (19.5m)	51.7 (23.5 kg)
<b>Delineate</b> (MW-XX-T)	0.4" x 4 1/4" x 8' (10.2mm x 10.8cm x 2.44m)	6	48 (14.6m)	43.2 (19.6 kg)
<b>Diplomat</b> (MW-XX-A)	3/8" x 4 1/2" x 8' (9.52mm x 11.43cm x 2.44m)	6	48 (14.6m)	43.2 (19.6 kg)
<b>Equinox</b> (MW-XX-R)	3/8" x 4 1/2" x 8' (9.53mm x 11.43 cm x 2.44m)	5	40 (12.2 m)	45 (20.4 kg)
<b>Exhibit</b> (MW-XX-FS)	1/4" x 4 1/4" x 8' (6.35mm x 10.8cm x 2.44m)	8	64 (19.5m)	46.5 (21.1 kg)
<b>Exhibit</b> (MW-XX-FS6)	1/4" x 6" x 8' (6.35mm x 15.24cm x 2.44m)	8	64 (19.5m)	61 (27.7 kg)
<b>Exhibit</b> (MW-XX-FS8)	1/4" x 8" x 8' (6.35mm x 20.32 cm x 2.44m)	4	32 (9.8m)	44 (20.0 kg)
<b>Inflection</b> (MW-XX-G)	3/8" x 5 1/4" x 8' (9.52mm x 13.34 cm x 2.44m)	6	48 (14.6m)	62 (28.1 kg)
<b>Ledge</b> (MW-XX-X62)	0.35" x 6" x 8' (8.89mm x 15.24cm x 2.44m)	5	40 (12.2m)	58 (26.3 kg)

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
<b>Mandalay</b> (MW-XX-H25)	3/8" x 2 1/2" x 8' (9.52mm x 6.35cm x 2.44m)	5	40 (12.2 m)	26.7 (12.1 kg)
<b>Mandalay</b> (MW-XX-H3)	3/8" x 3" x 8' (9.52mm x 7.62cm x 2.44m)	7	56 (17.1 m)	44.9 (20.4 kg)
<b>Mandalay</b> (MW-XX-H)	3/8" x 4 1/2" x 8' (9.53mm x 11.43cm x 2.44m)	5	40 (12.2 m)	48.7 (22.1 kg)
<b>Mandalay</b> (MW-XX-H6)	3/8" x 6" x 8' (9.53mm x 15.24cm x 2.44m)	4	32 (9.8 m)	53.4 (24.2 kg)
<b>Monarch</b> (MW-XX-M)	3/16" x 6" x 8' (4.76mm x 15.24cm x 2.44m)	6	48 (14.6 m)	48.3 (21.9 kg)
<b>Monument</b> (MW-XX-S25)	1/4" x 2.5" x 8' (6.35mm x 6.35cm x 2.44m)	8	64 (19.5m)	29.8 (13.5 kg)
<b>Monument</b> (MW-XX-S4)	1/4" x 4" x 8' (6.35mm x 10.16cm x 2.44m)	8	64 (19.5m)	48 (21.8 kg)
<b>Oblique</b> (MW-XX-N)	3/8" x 3" x 8' (9.52mm x 7.62cm x 2.44m)	7	56 (17.1 m)	41.1 (18.6 kg)
<b>Outline</b> (MW-XX-D)	5/16" x 3 1/2" x 8' (7.94mm x 8.89cm x 2.44m)	10	80 (24.4 m)	46 (20.9 kg)
<b>Recessed</b> (MW-XX-X63)	0.35" x 6" x 8' (8.89mm x 15.24cm x 2.44m)	5	40 (12.2m)	50 (22.7 kg)
<b>Reveal</b> (MW-XX-F)	1/4" x 4 1/4" x 8' (6.35mm x 10.8cm x 2.44m)	8	64 (19.5m)	49.7 (22.5 kg)
<b>Reveal</b> (MW-XX-F6)	1/4" x 6" x 8' (6.35mm x 15.24cm x 2.44m)	8	64 (19.5m)	66 (29.9 kg)
<b>Reveal</b> (MW-XX-F8)	1/4" x 8" x 8' (6.35mm x 20.32 cm x 2.44m)	4	32 (9.8 m)	47.8 (21.7 kg)
<b>Silhouette</b> (MW-XX-J)	1/2" x 4" x 8' (12.7mm x 10.16cm x 2.44m)	6	48 (14.6m)	39.3 (17.8 kg)
<b>Stance</b> (MW-XX-X60)	0.35" x 4 1/2" x 8' (8.89mm x 11.43cm x 2.44m)	5	40 (12.2m)	33 (15.0 kg)
<b>Stance</b> (MW-XX-X61)	0.35" x 6" x 8' (8.89mm x 15.24cm x 2.44m)	5	40 (12.2m)	45 (20.4 kg)

### 1.3.3. Physical Characteristics (Chair Rail & Corner Guard):

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
<b>Rampart</b> (CHR-XX-C)	3/8" x 4" x 8' (9.52mm x 10.16cm x 2.44m)	5	40 (12.2 m)	36 (16.3 kg)
<b>VBG-XX-C</b>	1/4" thick 90° profile with 1 1/4" (3.18cm) return legs x 8'	10	80 (24.4 m)	30 (13.6 kg)

## Tarkett North America

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)



**Millwork® Wall Finishing System**  
**Wallbase, Chair Rail, Corner Guard, and Quarter Round & Shoe Moulding**

**Product Specification**

1.3.4. **Physical Characteristics** (Quarter Round/Shoe Moulding):

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
QTR-XX-A	1/2" wide x 1/2" radius x 8' (12.7mm x 12.7mm x 2.44m) With pre-applied, pressure sensitive adhesive backing	20	160 (48.8 m)	25 (11.3 kg)
QTR-XX-D	3/4" wide x 3/4" radius x 8' (19.05mm x 19.05mm x 2.44m) With pre-applied, pressure sensitive adhesive backing	10	80 (24.4 m)	27 (12.2 kg)
SHU-XX-A	1/4" wide x 1 1/2" x 8' (6.35mm x 3.81cm x 2.44m) With pre-applied, pressure sensitive adhesive backing	10	80 (24.4 m)	19 (8.6 kg)

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.2. Millwork Wall Base meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.
- 2.3. **Flexibility:** Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.
- 2.4. **Chemical resistance** (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution
- 2.5. **Resistance to light** (ASTM F 1515): ΔE < 8
- 2.6. **Fire Resistance:** (ASTM E 648) Critical Radiant Flux (NFPA 253): Class I
- 2.7. **CAN/ULC-S102.2:** FSR 48 / SDV 366

**3. AVAILABILITY AND COST**

For availability and cost contact authorized Tarkett distributors nationwide.

**4. INSTALLATION**

- 4.1 See Tarkett Millwork Wall Finishing Systems or Chair Rail installation instructions for complete details.
- 4.2. **Adhesives:**

Quarter Round (QTR XX A, QTR XX D) and Shoe Moulding (SHU XX A) are self-stick accessories designed for application to Tarkett Millwork and do not require additional adhesives.

- **Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)**  
 Application: Brush or roller

Approximate coverage:

Base Height	1 qt. unit:	1 gal. unit:
2.5"	115-173 lf.	692-1034 lf.
3"	96-144 lf.	576-860 lf.
3 1/2"	81-123 lf.	493-736 lf.
4"	72-108 lf.	432-646 lf.
4 1/4"	68-102 lf.	407-607 lf.
4 1/2"	64-96 lf.	384-573 lf.
6"	48-72 lf.	288-430 lf.
8"	36-54 lf.	215-322 lf.

• **Tarkett 960 Cove Base Adhesive (Porous surfaces)**

Application: 1/8x1/8x1/8 SQ-notch trowel

Approximate Coverage:

Base Height	1 gal unit
2.5"	300-350 lf.
3"	275-325 lf.
3 1/2"	230-280 lf.
4"	200-250 lf.
4 1/4"	185-235 lf.
4 1/2"	175-225 lf.
6"	100-150 lf.
8"	100-125 lf.

**5. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Millwork Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical Support at (800) 899-8916 or E-mail:

[Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. LIMITED WARRANTY**

Limited 2-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**Tarkett North America**

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)